

PINE GROVE GOLD PROPERTY

**DRILL RESULTS 2009-2010
PROGRAM ENDING FEBRUARY 2010**

Explanation ozs Gold Per Ton

	0.010 to 0.029
	0.030 to 0.049
	0.050 to 0.099
	=> 0.100

WILSON DEPOSIT

Drill Hole	T.D. (ft)	Angle	Azimuth	From	To	Intercept	opt Au	g/t Au
WL-63	375	-90	NA	60	65	5	0.012	0.41
				70	75	5	0.011	0.38
				105	120	15	0.018	0.62
				180	195	15	0.087	2.98
				255	270	15	0.026	0.89
				290	305	15	0.027	0.93
				315	320	5	0.010	0.34
WL-64	390	-90	NA <i>including and</i>	185	190	5	0.010	0.34
				220	235	15	0.145	4.97
				220	225	5	0.135	4.63
				230	235	5	0.275	9.43
				310	315	5	0.021	0.72
WL-65	355	-90	NA	65	100	35	0.038	1.30
				225	230	5	0.026	0.89
				325	330	5	0.011	0.39
WL-66	295	-90	NA <i>including</i>	125	165	40	0.047	1.61
				150	155	5	0.155	5.31
WL-67	255	-90	NA	75	80	5	0.096	3.29
				90	110	20	0.024	0.82
				140	150	10	0.029	0.99
WL-68	375	-90	NA <i>including</i>	180	200	20	0.123	4.22
				180	185	5	0.378	12.96
				250	265	15	0.037	1.27
				365	375	10	0.013	0.45

PINE GROVE GOLD PROPERTY

**DRILL RESULTS 2009-2010
PROGRAM ENDING FEBRUARY 2010**

WL-70	355	-90	NA	320	340	20	0.016	0.55
WL-71	355	-90	NA	135	145	10	0.016	0.55
				155	165	10	0.040	1.37
				285	315	30	0.033	1.13
			<i>including</i>	305	310	5	0.111	3.81
WL-72	355	-90	NA	100	105	5	0.019	0.65
				195	200	5	0.014	0.48
				230	235	5	0.030	1.03
WL-73	375	-90	NA	10	25	15	0.027	0.93
				125	130	5	0.037	1.27
				170	175	5	0.020	0.69
				205	210	5	0.012	0.41
WL-74	355	-90	NA	180	190	10	0.085	2.91
			<i>including</i>	180	185	5	0.108	3.70
WL-75	295	-90	NA	150	155	5	0.122	4.18
				160	165	5	0.011	0.38
WL-76	295	-90	NA	155	160	5	0.014	0.48
				170	175	5	0.013	0.45
				215	225	10	0.043	1.47
WL-77	295	-90	NA	110	115	5	0.019	0.65
				175	180	5	0.057	1.95
WL-79	255	-45	180	60	65	5	0.013	0.45
				75	80	5	0.012	0.41
				110	115	5	0.055	1.89
				160	165	5	0.014	0.48
WL-80	275	-90	NA	0	15	15	0.012	0.41
			Dump	60	65	5	0.010	0.34

PINE GROVE GOLD PROPERTY

**DRILL RESULTS 2009-2010
PROGRAM ENDING FEBRUARY 2010**

				180	185	5	0.062	2.13
				200	205	5	0.519	17.80
				215	220	5	0.385	13.20
				235	240	5	0.011	0.38
WL-82	295	-45	180	25	30	5	0.021	0.72
				55	60	5	0.014	0.48
WL-83	275	-45	180	75	80	5	0.083	2.85
				160	165	5	0.011	0.38
				175	180	5	0.010	0.34
				245	247	2	0.018	0.62
			<i>including</i>	255	270	15	0.059	2.02
				260	265	5	0.142	4.87
WL-84	230	-90	NA	130	140	10	0.024	0.82
				180	190	10	0.058	1.99
WL-85	250	-90	NA	155	165	10	0.140	4.80
				205	210	5	0.024	0.82
WL-86	250	-45	180	5	15	10	0.021	0.72
				95	100	5	0.028	0.96
WL-87	150	-90	NA	70	75	5	0.012	0.41
				80	85	5	0.015	0.51
				90	95	5	0.016	0.55
				100	105	5	0.017	0.58
WL-88	190	-45	180	40	45	5	0.016	0.55
				60	80	20	0.021	0.72
				130	135	5	0.032	1.10
WL-89	190	-45	180	5	25	20	0.056	1.92
			<i>including</i>	5	10	5	0.141	4.83
				45	50	5	0.013	0.45
				110	120	10	0.036	1.23
				150	155	5	0.031	1.06
				180	190	10	0.426	14.61

PINE GROVE GOLD PROPERTY

**DRILL RESULTS 2009-2010
PROGRAM ENDING FEBRUARY 2010**

			<i>including</i>	180	185	5	0.820	28.12
WL-90	190	-90	NA	90	100	10	0.020	0.69
WL-91	190	-90	NA	140 160	150 165	10 5	0.038 0.010	1.30 0.34
WL-92	190	-90	NA <i>including</i>	65 80 90 110	70 100 95 140	5 20 5 30	0.014 0.036 0.106 0.046	0.48 1.23 3.63 1.58
WL-93	250	-60	180	65 90	85 100	20 10	0.023 0.034	0.79 1.17
WL-94	190	-90	NA	65 125 140	70 130 150	5 5 10	0.011 0.095 0.011	0.38 3.26 0.38
WL-95	150	-90	NA	15	20	5	0.087	2.98
WL-96	110	-90	NA	10 70	15 75	5 5	0.031 0.022	1.06 0.75
WL-97	265	-90	NA <i>including</i>	65 105 105	70 115 110	5 10 5	0.041 0.667 1.170	1.41 22.87 40.12
WL-98	170	-90	NA	5 85 105 135	30 90 110 140	25 5 5 5	0.020 0.075 0.041 0.093	0.69 2.57 1.41 3.19
WL-99	250	-90	NA	85 135	121 140	36 5	0.022 0.033	0.75 1.13
WL-100	330	-90	NA	60	95	35	0.020	0.69

PINE GROVE GOLD PROPERTY

**DRILL RESULTS 2009-2010
PROGRAM ENDING FEBRUARY 2010**

				130	135	5	0.197	6.76
				275	295	20	0.018	0.62
				325	330	5	0.018	0.62
WL-101	210	-90	NA including and	95	101	6	0.051	1.75
				110	130	20	0.112	3.84
				110	115	5	0.117	4.01
				125	130	5	0.208	7.13
				160	170	10	0.075	2.57
WL-102	170	-90	NA <i>including</i>	55	65	10	0.076	2.61
				55	60	5	0.134	4.59
				120	124	4	0.041	1.41
				150	155	5	0.017	0.58
WL-103	366	-70	180 <i>Stope backfill</i>	95	100	5	0.020	0.69
				125	130	5	0.034	1.17
				140	150	10	0.035	1.20
				270	280	10	0.059	2.02

WHEELER DEPOSIT

Drill Hole	T.D. (ft)	Angle	Azimuth	From	To	Intercept	opt Au	g/t Au
WR-98	270	-90	NA	240	245	5	0.014	0.48
WR-99	450	-45	245	230	250	20	0.039	1.34
				295	210	15	0.024	0.82
WR-101	250	-90	NA	115	140	25	0.021	0.72
				155	160	5	0.020	0.69
WR-102	350	-90	NA <i>including</i>	55	80	25	0.040	1.37
				70	75	5	0.107	3.67
				150	155	5	0.011	0.38
				215	220	5	0.013	0.45
				240	245	5	0.179	6.14
				270	275	5	0.012	0.41

PINE GROVE GOLD PROPERTY

**DRILL RESULTS 2009-2010
PROGRAM ENDING FEBRUARY 2010**

WR-103	290	-90	NA	45	50	5	0.018	0.62
WR-104	180	-90	NA <i>including</i>	60 65	70 70	10 5	0.118 0.220	4.05 7.54
WR-105	250	-90	NA	45 110 170	65 115 175	20 5 5	0.035 0.032 2.250	1.20 1.10 77.15
WR-106	250	-90	NA <i>including</i> <i>including</i> <i>including</i> <i>including</i> <i>including</i> <i>and</i>	0 0 55 55 102 105 140 160 190	40 5 95 60 110 110 210 170 200	40 5 40 5 8 5 70 10 10	0.195 0.638 0.028 0.122 0.096 0.129 0.078 0.194 0.118	6.69 21.88 0.96 4.18 3.29 4.42 2.67 6.65 4.05
WR-107	200	-90	NA	40 55 115	45 60 125	5 5 10	0.022 0.011 0.019	0.75 0.38 0.65
WR-108	210	-90	NA	85 105	90 125	5 20	0.099 0.036	3.39 1.23
WR-109	210	-90	NA	0 55 105	5 75 110	5 20 5	0.101 0.028 0.041	3.46 0.96 1.41
WR-110	170	-90	NA <i>including</i>	10 30 35	13 100 40	3 70 5	0.021 0.044 0.101	0.72 1.51 3.46
WR-111	250	-90	NA	175	185	10	0.042	1.44
WR-113	210	-90	NA <i>including</i>	110 115	135 120	25 5	0.057 0.113	1.95 3.87

PINE GROVE GOLD PROPERTY

**DRILL RESULTS 2009-2010
PROGRAM ENDING FEBRUARY 2010**

WR-114	250	-90	NA <i>including</i>	0	15	15	0.149	5.11
				0	10	10	0.199	6.82
				125	140	15	0.017	0.58
				150	155	5	0.035	1.20
				175	180	5	0.097	3.33
				210	215	5	0.019	0.65
WR-116	250	-90	NA <i>including</i>	10	70	60	0.043	1.47
				45	50	5	0.245	8.40
				180	185	5	0.079	2.71
				200	205	5	0.012	0.41
WR-117	170	-90	NA <i>including</i>	85	95	10	1.344	46.09
				85	90	5	2.270	77.84
WR-118	310	-90	NA <i>including</i>	0	5	5	0.012	0.41
				15	35	20	0.016	0.55
				90	95	5	0.015	0.51
				110	140	30	0.022	0.75
				150	170	20	0.025	0.86
				195	230	35	0.035	1.20
				215	220	5	0.104	3.57
255	260	5	0.082	2.81				
WR-119	210	-90	NA <i>including</i>	25	95	70	0.096	3.29
				35	55	20	0.175	6.00
				125	130	5	0.013	0.45